



Technical Data Sheet

PPC No. 440 WHITE ALUMINIUM FOIL TAPE

DESCRIPTION: A WHITE FOIL / POLYPROPYLENE FACING TAPE FOR JOINING SIMILAR MATERIALS

TECHNICAL DATA:

BACKING	LAMINATED POLYPROPYLENE TO ALUMINIUM FOIL
TENSILE STRENGTH	24.5 N/25mm
ADHESIVE TYPE	SYNTHETIC RUBBER/RESIN
ADHESION TO STEEL	20 N/25mm
ELONGATION AT BREAK	25%
TOTAL THICKNESS WITHOUT LINER	95 MICRONS (μm)
TEMPERATURE RANGE	-5°C UP TO 65°C

50 METRE ROLL LENGTHS

AVAILABLE WIDTHS	NUMBER OF ROLLS PER CARTON
48MM	20
72MM	16

APPLICATION NOTE:

It is recommended that surfaces to which the tape is to be applied are cleaned with mineral turpentine and allowed to dry before application

PRECISION PAPER COATINGS PTY LTD PH: +61 (02) 9780 9000 FAX +61(02) 97289966

The detail in this leaflet refers to average test results obtained in our laboratory out of samples chosen from average production. The results are purely indicative and it is recommended that the user independently ascertain suitability for the application.