



# Technical Data Sheet

## PPC No. 876 BLACK REINFORCED ALUMINIUM FOIL TAPE

### DESCRIPTION:

THE UNIQUE NATURE OF THE BACKING GIVES THIS PRODUCT A RARE COMBINATION OF HIGH STRENGTH, FLEXIBILITY AND CONFORMABILITY. THE PRESSURE SENSITIVE ADHESIVE SYSTEM IS FORMULATED FOR HIGH HOLDING POWER.

### TECHNICAL DATA:

BACKING	LAMINATED POLYETHYLENE FILM POLYETHYLENE FIBRE MESH ALUMINIUM FOIL WHITE INKED FINISH
TENSILE STRENGTH	100 N/25mm
ADHESIVE TYPE	SYNTHETIC RUBBER/RESIN
ADHESION TO STEEL	20 N/25mm
ELONGATION AT BREAK	25%
TOTAL THICKNESS WITHOUT LINER	205 MICRONS ( $\mu\text{m}$ )
TEMPERATURE RANGE	-5°C UP TO 65°C

### 50 METRE ROLL LENGTHS

AVAILABLE WIDTHS	NUMBER OF ROLLS PER CARTON
48MM	20
63MM	16
72MM	16
96MM	12
120MM	8

#### APPLICATION NOTE:

It is recommended that surfaces to which the tape is to be applied are cleaned with mineral turpentine and allowed to dry before application

**PRECISION PAPER COATINGS PTY LTD PH: +61 (02) 9780 9000 FAX +61(02) 97289966**

The detail in this leaflet refers to average test results obtained in our laboratory out of samples chosen from average production. The results are purely indicative and it is recommended that the user independently ascertain suitability for the application.