



# PRODUCT DATA SHEET

Product Code: # 409  
Product Type: Cloth Tape  
Carrier/Construction: P.E. Coated Polyester / Cotton Cloth  
Adhesive: High Shear Rubber

## TYPICAL PHYSICAL PROPERTIES

Peel Adhesion to Steel: 8N/25mm  
Tensile: 13 Kg/25mm  
Elongation at Break: 11%  
Adhesive Coat Weight: 210gsm  
Application Temperature: 0 to 35°C  
Service Temperature: 10 to 40°C  
Cloth Composition: 65% Polyester, 35% Cotton  
Cloth Warp and Weft: 30 and 35 +/-2 threads per 25mm  
Core Material: Paper  
Inner Core Diameter: 76mm +/- 1  
Storage life: 6 months  
Recommended Storage Temperature: 20 – 30 degrees C

## APPLICATIONS

Ideal for joining diverse materials; packing; holding; sandblasting; sealing and joining flexible ductwork.

Colours: Various colours available  
Sizes: 48mm x 25M 30 Rolls per carton  
72mm x 25M 24 Rolls per carton

## PRECISION PAPER COATINGS PTY LTD

PH: (02) 9780 9000 FAX: (02) 9728 9966

April 2010

The detail in this leaflet refers to average test results obtained in our laboratory out of sample chosen from average production. The results are purely indicative and it is recommended that the user independently ascertain suitability for the application.