

COMPANY DETAILS

PRECISION PAPER COATINGS PTY LTD
25 MIOWERA ROAD, VILLAWOOD NSW 2163
P.O. BOX 654 CHESTER HILL NSW 2162

ABN: 3000 845 518
PHONE: (02) 9780 9000
FAX: (02) 9728 9966
E-MAIL: info@ppcpl.com.au

IDENTIFICATION

PRODUCT NAME: PPC No. 441 HEAVY DUTY PVC TAPE
OTHER NAME (S): NIL
IDENT NUMBER (S): NIL

UN NUMBER: FREE
DANGEROUS GOODS CLASS: N/A
PACKAGING GROUP: N/A
SUBSIDIARY RISK: NOT APPLICABLE
HAZCHEM CODE: NOT APPLICABLE
POISON SCHEDULE: NOT APPLICABLE

USE: GENERAL PURPOSE AIR AND WATER SEALANT

PHYSICAL DESCRIPTION/PROPERTIES

APPEARANCE: LINERLESS PVC TAPE
ODOUR: NO ODOUR
BOILING/MELTING POINT: N/A VAPOUR PRESSURE: N/A
DENSITY: N/A FLASHPOINT: N/A
FLAMMABILITY: N/A SOLUBILITY IN WATER: NOT SOLUBLE
SPECIFIC GRAVITY (H₂O= 1): 1.25 – 1.45
DECOMPOSITION TEMPERATURE 260⁰C (500F)

INGREDIENTS

<u>CHEMICAL IDENTITY:</u>	<u>CAS No.</u>	<u>PROPORTION %</u>
RUBBER ADHESIVE	N/A	8-12
PVC RESIN	9002-86-2	62-66
PLASTICISER (DEHP)	117-81-7	23-27
LEAD COMPOUND	7439-92-1	0.8
TOLUENE	108-88-3	0-1.5

HEALTH HAZARD INFORMATION

HEALTH EFFECTS - ACUTE

SWALLOWED: NONE APPLICABLE UNDER TRAINED INDUSTRY USAGE
EYE: NONE APPLICABLE UNDER TRAINED INDUSTRY USAGE
SKIN: NONE APPLICABLE UNDER TRAINED INDUSTRY USAGE
INHALED: NONE APPLICABLE UNDER TRAINED INDUSTRY USAGE

HEALTH EFFECTS - CHRONIC NONE KNOWN

FIRST AID

SWALLOWED: NONE APPLICABLE UNDER TRAINED INDUSTRY USAGE
EYE: NONE APPLICABLE UNDER TRAINED INDUSTRY USAGE
SKIN: NONE APPLICABLE UNDER TRAINED INDUSTRY USAGE
INHALED: NONE APPLICABLE UNDER TRAINED INDUSTRY USAGE

ADVICE TO DOCTOR: NOT APPLICABLE UNDER TRAINED INDUSTRY USAGE

PRECAUTIONS FOR USE

EXPOSURE STANDARDS: NOT APPLICABLE

ENGINEERING CONTROLS:

THIS IS A TAPE CONSTRUCTED FROM STRONG MATERIAL. AS SUCH, THE FOLLOWING ARE POINTED OUT TO THE USERS OF THIS PRODUCT: -

1. THE TAPE IS A "TOUGH" CONSTRUCTION. TAKE CARE NOT TO BE CUT BY EDGES DURING APPLICATION.

PERSONAL PROTECTION

USERS WHO ARE UNDERGOING TRAINING IN PROPER USE MAY BE ADVISED TO USE PROTECTIVE GLOVES UNTIL JUDGED FULLY TRAINED IN THE USE AND APPLICATION OF THE PRODUCT.

THE ABOVE ENGINEERING CONTROLS SHOULD BE MADE ADEQUATELY CLEAR TO ALL USERS.

FLAMMABILITY

FLASHPOINT (ASTM D-1929): 320-390°C
SOFTENING POINT 80°C

KEEP AWAY FROM SOURCES OF IGNITION: YES
USE ONLY IN FLAMEPROOF AREA: NO

HAZARDOUS MELTING AND DRIPPING MAY OCCUR AT HIGH TEMPERATURES, VINYL MAY BE FORCED TO BURN CONTINUOUSLY BY APPLICATION OF HEAT

SPECIAL FIRE FIGHTING PROCEDURES: WHEN ENTERING ENCLOSED AREA, FIRE FIGHTER SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS

EXTINGUISHING MEDIA WATER, DRY FOAM, CO₂

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT

GENERAL: NO SPECIAL REQUIREMENTS

STORAGE: STORE IN ORIGINAL CONTAINER AT ROOM TEMPERATURE, AWAY FROM SOURCES OF FLAME OR HEAT

UN NUMBER: FREE
DG CLASS & SUBSIDIARY RISK: NOT APPLICABLE
PACKAGING GROUP: NOT APPLICABLE
HAZCHEM CODE: NOT APPLICABLE
IATA CLASS: FREE
IMDG REFERENCE: FREE
INCOMPATIBLE DG CLASSES: NONE KNOWN
INCOMPATIBLE RECEPTACLE: NONE KNOWN
INCOMPATIBLE SUBSTANCES: NONE KNOWN

EMERGENCY PROCEDURE GUIDE DATE: NOT APPLICABLE

HANDLING: SEE ENGINEERING CONTROLS ABOVE

WHOLESALE-CARTONED PRODUCT: NOT APPLICABLE

AT SITE USE PRODUCT: SEE ENGINEERING CONTROLS ABOVE

SPILLS & DISPOSAL

THIS IS A STABLE MANUFACTURED PRODUCT. SPILLS WOULD NORMALLY REQUIRE ONLY COLLECTION OF SPILT MATERIAL.

DISPOSAL IS SUBJECT TO LOCAL STATE WASTE REGULATIONS.

FIRE/EXPLOSION HAZARD

EXTINGUISHING MEDIA: WATER, FOAM, CO2

THERMAL DECOMPOSITION & BURNING MAY RELEASE OXIDES OF CARBON & OTHER TOXIC GASES OR VAPOURS (INCLUDING HCl). DO NOT RELEASE CHEMICALLY CONTAMINATED WATER INTO DRAINS, SOIL OR SURFACE WATERS. SUFFICIENT MEASURES MUST BE TAKEN TO RETAIN WATER USED FOR EXTINGUISHING. DISPOSE OF CONTAMINATED WATER AND SOIL ACCORDING TO LOCAL REGULATIONS.

OTHER INFORMATION

ENVIRONMENTAL DATA: NOT APPLICABLE

FISH TOXICITY: NOT AVAILABLE
TOXICITY TO BACTERIA: NOT AVAILABLE
OECD BIOLOGICAL DEGRADATION: NOT AVAILABLE

FURTHER INFORMATION

SINCE WE CANNOT ANTICIPATE OR CONTROL THE MANY DIFFERENT CONDITIONS UNDER WHICH THIS INFORMATION AND THIS PRODUCT MAY BE USED, EACH SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED APPLICATION AND CONFIRM THAT THEY ARE APPROPRIATE.

CONTACT POINT

PLEASE CONTACT: LABORATORY MANAGER
PHONE: (02) 9780 9000

AUTHORISED BY: R . LEVOT DATE: 10-08-2011