



Technical Data Sheet

No. 338 Double Sided Scrim Tape

Applications:

Constructed from a very flexible, high density, fine polyethylene non-woven reinforced scrim. Both sides are coated with a heavy layer of aggressive adhesive. Each roll is wound with a release liner for ease of handling, application and adhesive protection. Easy to tear by hand.

This combination of flexible backing and heavy adhesive coating is designed to conform and stick to most surfaces, making it ideal to assist in laying carpet, linoleum and carpet tiles. This versatile product is also useful for joining overlapped edges of foil-faced reflective sheeting (Sarking), giving moisture and dust-proof joints under roofs and inside gables

Technical Data:

BACKING MATERIAL	High-Density Polyethylene Scrim
TOTAL THICKNESS WITHOUT LINER	185 Microns (μm)
ADHESIVE TYPE	Synthetic Rubber/ Resin
ADHESION TO STEEL	35 N/25mm
TENSILE STRENGTH	105 N/25mm
ELONGATION AT BREAK	15%
TEMPERATURE RANGE	-5 UP TO 70°C

25 METRE ROLL LENGTHS:

STANDARD WIDTHS	NUMBER OF ROLLS PER CARTON
18mm	48
24mm	36
36mm	24
48mm	20

PRECISION PAPER COATINGS PTY LTD PH: +61 (02) 9780 9000 FAX +61 (02) 9728 9966

The detail in this leaflet refers to average test results obtained in our laboratory out of samples chosen from average production. The results are purely indicative and it is recommended that the user independently ascertain suitability for the application.