



# Technical Data Sheet

## No. 760 Double-Sided Tissue Tape

### CONSTRUCTION:

**Tissue Paper:** 14 gsm  
**Adhesive:** Solvent based acrylic adhesive.  
**Release Liner:** Silicone release PE-coated paper, white colour 105 gsm.

### TYPICAL PHYSICAL PROPERTIES:

**Total Thickness ( without release liner ):** 100 micron  
**Holding power:** > 800 mins.  
**Peel Adhesion (Av):** 15 – 20 N/25mm (20 min dwell on stainless steel)  
**Adhesion to liner:** ≤0.5 N/25mm

### PACKING:

**Core I.D.:** 3" (76mm ±1)  
**Jumbo Roll:** 1.04 x 1000m; 1.04 x 850m, 1.04 x 500m  
**Packaging:** Wrapped with corrugated cardboard.  
**Cut Roll:** Roll width 3mm up

### REMARKS:

- 1. Tolerance : Weight and Thickness: ±10%; Width: ± 3mm;  
Length: Cut Roll & Log Roll ± 03.m, Jumbo Roll ± 0.5%**
- 2. The products should be stored at room temperature and be kept away wet and/or heat source.**
- 3. It is essential, as with all pressure – sensitive tapes \, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.**
- 4. The users should take test and do trial-application on the above products before coming into application so as to witness and ensure suitability for their special purpose and technique.**

**PRECISION PAPER COATINGS PTY LTD PH: +61 (02) 9780 9000 FAX +61 (02) 9728 9966**

The detail in this leaflet refers to average test results obtained in our laboratory out of samples chosen from average production. The results are purely indicative and it is recommended that the user independently ascertain suitability for the application.

**PRECISION PAPER COATINGS PTY LTD PH: +61 (02) 9780 9000 FAX +61 (02) 9728 9966**

The detail in this leaflet refers to average test results obtained in our laboratory out of samples chosen from average production. The results are purely indicative and it is recommended that the user independently ascertain suitability for the application.