



PPC #5703

White Double Sided EVA Tape



High Shear Strength – Acrylic Adhesive – Good Tensile Strength

Product Construction:

A high density EVA with a solvent based acrylic adhesive

Product Dimensions:-

- 3.2mm thick ~ in widths from 9mm – 1000mm

Product Information:

- High density foam providing good internal sheer strength.
- Good combination of high initial tack and long term bond strength.
- Excellent for medium demand applications.

Applications

- Widely applied on signs, nameplate, purchase display, book rack, photo frame and cable clip

PRECISION PAPER COATINGS PTY LTD

25 MOWERA ROAD, VILLAWOOD NSW 2163 AUSTRALIA

TEL: 61 2 9780 9000

FAX: 61 2 9728 9966

www.ppcpl.com.au



PPC #5703

White Double Sided EVA Tape

Technical Data Information

Physical Properties:

Carrier	Hi Density White EVA Foam
Adhesive	Solvent based acrylic adhesive
Thickness	3.2±0.15

Performance Characteristics:

Item	Result	Standard Test Procedure
Initial Adhesion	≥16N/25mm	FINAT/FTM9
Holding Power	≥24h	GB/T 4851 (1Kg)
Temp Resistance in application	-5~80°C	GB/T 2941-91

Application:

Application Temperature	Above 10 degrees C
Surface preparation	Clean surface to remove any moisture, oil, dust or surface contaminant
Application of product	Apply firm pressure to increase bond.
Clean up.	Dispose of waste in recycle receptacle

Storage:

Temperature	Moderate Conditions
Shelf Life	1 year in sealed carton.

PPC do not make specific performance claims regarding this product. Before purchasing, you should request a sample of this tape to test and satisfy yourself that this tape is suitable in your specific application.

PRECISION PAPER COATINGS PTY LTD

25 MOWERA ROAD, VILLAWOOD NSW 2163 AUSTRALIA

sales@ppcpl.com.au

TEL: 61 2 9780 9000 FAX: 61 2 9728 9966

www.ppcpl.com.au