



Technical Data Sheet

No. 334 Double Sided Cloth Tape

Applications:

Constructed from Bleached Cotton Cloth, coated both sides with a heavy layer of aggressive synthetic rubber adhesive. Each roll is wound with a release liner for ease of handling and application.

The combination of cloth material and heavy adhesive coating is designed for permanent installation of carpet, linoleum and carpet tiles. Other applications include fixing grips to sporting equipment, mounting of printing plates, signs and nameplates.

Technical Data:

BACKING MATERIAL	Cotton Cloth
TOTAL THICKNESS WITHOUT LINER	300 Microns (μm)
ADHESIVE TYPE	Synthetic Rubber/ Resin
ADHESION TO STEEL	28 N/25mm
TENSILE STRENGTH	120 N/25mm
ELONGATION AT BREAK	5.8%
TEMPERATURE RANGE	-15 UP TO 65°C

23 METRE ROLL LENGTHS:

STANDARD WIDTHS	NUMBER OF ROLLS PER CARTON
18mm	48
24mm	36
36mm	24
48mm	20

PRECISION PAPER COATINGS PTY LTD PH: +61 (02) 9780 9000 FAX +61 (02) 9728 9966

The detail in this leaflet refers to average test results obtained in our laboratory out of samples chosen from average production. The results are purely indicative and it is recommended that the user independently ascertain suitability for the application.